

BLANKING DIM. TS, 16th, AUGUST, 2012, PREPARED BY D. T., REL. BY M. S.

Traceability data				Blanking dimensions									
SIZE nominal	WEIGHT nominal	WALL nominal		OD-BOX Regular		OD-BOX Special Clearance		ID-BOX		EL-BOX minimal		IL-BOX minimal	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
inch	lb/ft	inch	mm	+ 0,020 - 0,010	+ 0,50 - 0,25	+ 0,020 - 0,010	+ 0,50 - 0,25	±0,010	± 0,25	inch	mm	inch	mm

2 3/8	4.6	0,190	4,83	2,707	68,75	2,628	66,75	1,939	49,25	3,504	89	3,307	84
2 3/8	5.1	0,218	5,54	2,736	69,50	2,628	66,75	1,939	49,25	3,504	89	3,307	84
2 3/8	5.8	0,254	6,45	2,785	70,75	2,707	68,75	1,939	49,25	3,504	89	3,307	84
2 7/8	6.4	0,217	5,51	3,240	82,30	3,159	80,25	2,384	60,55	3,819	97	3,622	92
2 7/8	7.7	0,276	7,01	3,337	84,75	3,274	83,15	2,384	60,55	3,819	97	3,622	92
2 7/8	8.6	0,308	7,82	3,364	85,45	3,274	83,15	2,333	59,25	3,819	97	3,622	92
2 7/8	9.8	0,362	9,19	3,435	87,25	3,337	84,75	2,270	57,65	3,819	97	3,622	92
3 1/2	7.7	0,216	5,49	3,841	97,55	---	---	3,022	76,75	4,291	109	4,055	103
3 1/2	9.2	0,254	6,45	3,900	99,05	3,803	96,60	3,022	76,75	4,291	109	4,055	103
3 1/2	10.2	0,289	7,34	3,961	100,60	3,862	98,10	2,982	75,75	4,291	109	4,055	103
3 1/2	12.7	0,375	9,53	4,079	103,60	3,961	100,60	2,935	74,55	4,291	109	4,055	103
3 1/2	13.7	0,413	10,49	4,138	105,10	4,045	102,75	2,844	72,25	4,291	109	4,055	103
3 1/2	15.5	0,449	11,40	4,193	106,50	4,045	102,75	2,732	69,40	4,291	109	4,055	103
3 1/2	15.8	0,476	12,09	4,211	106,95	4,138	105,10	2,732	69,40	4,291	109	4,055	103
4	9.5	0,226	5,74	4,348	110,45	---	---	3,502	88,95	4,528	115	4,331	110
4	10.9	0,262	6,65	4,407	111,95	4,327	109,90	3,502	88,95	4,528	115	4,331	110
4	13.0	0,330	8,38	4,516	114,70	4,366	110,90	3,467	88,05	4,528	115	4,331	110
4	14.8	0,380	9,65	4,606	117,00	4,469	113,50	3,356	85,25	4,528	115	4,331	110
4	16.5	0,430	10,92	4,656	118,25	---	---	3,356	85,25	4,528	115	4,331	110
4 1/2	10.5	0,224	5,69	4,862	123,50	4,813	122,25	3,994	101,45	4,961	126	4,764	121
4 1/2	11.6	0,250	6,35	4,862	123,50	4,813	122,25	3,994	101,45	4,961	126	4,764	121
4 1/2	12.6	0,271	6,88	4,892	124,25	4,813	122,25	3,994	101,45	4,961	126	4,764	121
4 1/2	13.5	0,290	7,37	4,961	126,00	4,813	122,25	3,994	101,45	4,961	126	4,764	121
4 1/2	15.1	0,337	8,56	5,010	127,25	4,892	124,25	3,943	100,15	4,961	126	4,764	121
4 1/2	16.9	0,380	9,65	5,106	129,70	---	---	3,864	98,15	4,961	126	4,764	121
4 1/2	18.8	0,430	10,92	5,146	130,70	---	---	3,864	98,15	4,961	126	4,764	121
4 1/2	21.6	0,500	12,70	5,280	134,10	---	---	3,685	93,60	4,961	126	4,764	121
4 1/2	24.6	0,560	14,22	5,333	135,45	---	---	3,685	93,60	4,961	126	4,764	121