

BLANKING DIM. TS, 16th, AUGUST; 2012, PREPARED BY D. T., REL. BY M. S.

Traceability data				Blanking dimensions							
SIZE nominal	WEIGHT nominal	WALL nominal		OD-PIN		ID-PIN		EL-PIN minimal		IL-PIN minimal	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
inch	lb/ft	inch	mm	+ 0,020 - 0	+ 0,50 - 0	+ 0 - 0,020	+ 0 - 0,5	inch	mm	inch	mm

2 3/8	4.6	0,190	4,83	2,383	60,5	1,949	49,5	2,638	67	2,520	64
2 3/8	5.1	0,218	5,54	2,383	60,5	1,939	49,3	2,638	67	2,520	64
2 3/8	5.8	0,254	6,45	2,383	60,5	1,867	47,4	2,638	67	2,520	64
2 7/8	6.4	0,217	5,51	2,883	73,2	2,396	60,9	2,953	75	2,835	72
2 7/8	7.7	0,276	7,01	2,883	73,2	2,323	59,0	2,953	75	2,835	72
2 7/8	8.6	0,308	7,82	2,883	73,2	2,259	57,4	2,953	75	2,835	72
2 7/8	9.8	0,362	9,19	2,883	73,2	2,151	54,6	2,953	75	2,835	72
3 1/2	7.7	0,216	5,49	3,513	89,2	3,035	77,1	3,386	86	3,268	83
3 1/2	9.2	0,254	6,45	3,513	89,2	2,992	76,0	3,386	86	3,268	83
3 1/2	10.2	0,289	7,34	3,513	89,2	2,922	74,2	3,386	86	3,268	83
3 1/2	12.7	0,375	9,53	3,513	89,2	2,750	69,9	3,386	86	3,268	83
3 1/2	13.7	0,413	10,49	3,513	89,2	2,674	67,9	3,386	86	3,268	83
3 1/2	15.5	0,449	11,40	3,513	89,2	2,602	66,1	3,386	86	3,268	83
3 1/2	15.8	0,476	12,09	3,513	89,2	2,548	64,7	3,386	86	3,268	83
4	9.5	0,226	5,74	4,013	101,9	3,518	89,4	3,661	93	3,543	90
4	10.9	0,262	6,65	4,013	101,9	3,476	88,3	3,661	93	3,543	90
4	13.0	0,330	8,38	4,013	101,9	3,340	84,8	3,661	93	3,543	90
4	14.8	0,380	9,65	4,013	101,9	3,240	82,3	3,661	93	3,543	90
4	16.5	0,430	10,92	4,013	101,9	3,140	79,8	3,661	93	3,543	90
4 1/2	10.5	0,224	5,69	4,513	114,6	4,010	101,9	4,094	104	3,976	101
4 1/2	11.6	0,250	6,35	4,513	114,6	4,000	101,6	4,094	104	3,976	101
4 1/2	12.6	0,271	6,88	4,513	114,6	3,958	100,5	4,094	104	3,976	101
4 1/2	13.5	0,290	7,37	4,513	114,6	3,920	99,6	4,094	104	3,976	101
4 1/2	15.1	0,337	8,56	4,513	114,6	3,826	97,2	4,094	104	3,976	101
4 1/2	16.9	0,380	9,65	4,513	114,6	3,740	95,0	4,094	104	3,976	101
4 1/2	18.8	0,430	10,92	4,513	114,6	3,640	92,5	4,094	104	3,976	101
4 1/2	21.6	0,500	12,70	4,513	114,6	3,500	88,9	4,094	104	3,976	101
4 1/2	24.6	0,560	14,22	4,513	114,6	3,380	85,9	4,094	104	3,976	101