



Blanking dimensions for TPS-Techniseal  
Casing-PIN-End on Accessories

TPS-OCTG

BLANKING DIM. TS, 09.01.2019, Rev.02, J.Stolz, EL-PIN / IL-PIN geändert, provided: D.Fuchs

Traceability data				Blanking dimensions							
SIZE nominal	WEIGHT nominal	WALL nominal		OD-PIN		ID-PIN		EL-PIN minimal		IL-PIN minimal	
inch	lb/ft	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
				+ 0,020 - 0	+ 0,50 - 0	+ 0 - 0,020	+ 0 - 0,5				
5	13.0	0,253	6,426	5,016	127,400	4,486	113,950	5,315	135,000	5,118	130,000
5	15.0	0,296	7,518	5,016	127,400	4,408	111,960	5,315	135,000	5,118	130,000
5	18.0	0,362	9,195	5,016	127,400	4,276	108,610	5,315	135,000	5,118	130,000
5	20.3	0,408	10,363	5,016	127,400	4,184	106,270	5,315	135,000	5,118	130,000
5	20.8	0,422	10,719	5,016	127,400	4,156	105,560	5,315	135,000	5,118	130,000
5	21.4	0,437	11,100	5,016	127,400	4,126	104,800	5,315	135,000	5,118	130,000
5	23.2	0,478	12,141	5,016	127,400	4,044	102,720	5,315	135,000	5,118	130,000
5	24.1	0,500	12,700	5,016	127,400	4,000	101,600	5,315	135,000	5,118	130,000
5 1/2	15.5	0,275	6,985	5,516	140,100	4,950	125,730	5,441	138,200	5,244	133,200
5 1/2	17.0	0,304	7,722	5,516	140,100	4,892	124,260	5,441	138,200	5,244	133,200
5 1/2	20.0	0,361	9,169	5,516	140,100	4,778	121,360	5,441	138,200	5,244	133,200
5 1/2	23.0	0,415	10,541	5,516	140,100	4,670	118,620	5,441	138,200	5,244	133,200
5 1/2	26.0	0,476	12,090	5,516	140,100	4,548	115,520	5,441	138,200	5,244	133,200
6 5/8	20.0	0,288	7,315	6,641	168,680	6,049	153,640	5,555	141,100	5,358	136,100
6 5/8	23.2	0,330	8,382	6,641	168,680	5,965	151,510	5,555	141,100	5,358	136,100
6 5/8	24.0	0,352	8,941	6,641	168,680	5,921	150,390	5,555	141,100	5,358	136,100
6 5/8	28.0	0,417	10,592	6,641	168,680	5,791	147,090	5,555	141,100	5,358	136,100
6 5/8	32.0	0,475	12,065	6,641	168,680	5,675	144,150	5,555	141,100	5,358	136,100
6 5/8	35.0	0,562	14,275	6,641	168,680	5,575	141,610	5,555	141,100	5,358	136,100
7	23.0	0,317	8,052	7,016	178,200	6,366	161,700	5,819	147,800	5,622	142,800
7	26.0	0,362	9,195	7,016	178,200	6,276	159,410	5,819	147,800	5,622	142,800
7	29.0	0,408	10,363	7,016	178,200	6,184	157,070	5,819	147,800	5,622	142,800
7	32.0	0,453	11,506	7,016	178,200	6,094	154,790	5,819	147,800	5,622	142,800
7	35.0	0,498	12,649	7,016	178,200	6,004	152,500	5,819	147,800	5,622	142,800
7	38.0	0,540	13,716	7,016	178,200	5,920	150,370	5,819	147,800	5,622	142,800
7	41.0	0,590	14,986	7,016	178,200	5,820	147,830	5,819	147,800	5,622	142,800
7	44.0	0,640	16,256	7,016	178,200	5,720	145,290	5,819	147,800	5,622	142,800
7	46.0	0,670	17,018	7,016	178,200	5,660	143,760	5,819	147,800	5,622	142,800
7 5/8	26.4	0,328	8,331	7,641	194,080	6,969	177,010	5,996	152,300	5,799	147,300
7 5/8	29.7	0,375	9,525	7,641	194,080	6,875	174,630	5,996	152,300	5,799	147,300
7 5/8	33.7	0,430	10,922	7,641	194,080	6,765	171,830	5,996	152,300	5,799	147,300
7 5/8	35.8	0,465	11,811	7,641	194,080	6,695	170,050	5,996	152,300	5,799	147,300
7 5/8	39.0	0,500	12,700	7,641	194,080	6,625	168,280	5,996	152,300	5,799	147,300
7 5/8	42.8	0,562	14,275	7,641	194,080	6,501	165,130	5,996	152,300	5,799	147,300
7 5/8	45.3	0,595	15,113	7,641	194,080	6,435	163,450	5,996	152,300	5,799	147,300
7 5/8	47.1	0,625	15,875	7,641	194,080	6,375	161,930	5,996	152,300	5,799	147,300
8 5/8	28.0	0,304	7,722	8,641	219,480	8,017	203,630	6,136	155,850	5,939	150,850
8 5/8	32.0	0,352	8,941	8,641	219,480	7,921	201,190	6,136	155,850	5,939	150,850
8 5/8	36.0	0,400	10,160	8,641	219,480	7,825	198,760	6,136	155,850	5,939	150,850
8 5/8	40.0	0,450	11,430	8,641	219,480	7,725	196,220	6,136	155,850	5,939	150,850
8 5/8	44.0	0,500	12,700	8,641	219,480	7,625	193,680	6,136	155,850	5,939	150,850
8 5/8	49.0	0,557	14,148	8,641	219,480	7,511	190,780	6,136	155,850	5,939	150,850
8 5/8	52.0	0,595	15,113	8,641	219,480	7,435	188,850	6,136	155,850	5,939	150,850
9 5/8	36.0	0,352	8,941	9,641	244,880	8,921	226,590	6,136	155,850	5,939	150,850
9 5/8	40.0	0,395	10,033	9,641	244,880	8,835	224,410	6,136	155,850	5,939	150,850
9 5/8	43.5	0,435	11,049	9,641	244,880	8,755	222,380	6,136	155,850	5,939	150,850
9 5/8	47.0	0,472	11,989	9,641	244,880	8,681	220,500	6,136	155,850	5,939	150,850
9 5/8	53.5	0,545	13,843	9,641	244,880	8,535	216,790	6,136	155,850	5,939	150,850
9 5/8	58.4	0,595	15,113	9,641	244,880	8,435	214,250	6,136	155,850	5,939	150,850
9 5/8	59.4	0,609	15,469	9,641	244,880	8,407	213,540	6,136	155,850	5,939	150,850
9 5/8	61.1	0,625	15,875	9,641	244,880	8,375	212,730	6,136	155,850	5,939	150,850
10 3/4	40.5	0,350	8,890	10,766	273,450	10,050	255,270	6,179	156,950	5,982	151,950
10 3/4	45.5	0,400	10,160	10,766	273,450	9,950	252,730	6,179	156,950	5,982	151,950
10 3/4	51.0	0,450	11,430	10,766	273,450	9,850	250,190	6,179	156,950	5,982	151,950
10 3/4	55.5	0,495	12,573	10,766	273,450	9,760	247,900	6,179	156,950	5,982	151,950
10 3/4	60.7	0,545	13,843	10,766	273,450	9,660	245,360	6,179	156,950	5,982	151,950
10 3/4	65.7	0,595	15,113	10,766	273,450	9,560	242,820	6,179	156,950	5,982	151,950
11 3/4	47.0	0,375	9,525	11,766	298,850	11,000	279,400	6,179	156,950	5,982	151,950
11 3/4	54.0	0,435	11,049	11,766	298,850	10,880	276,350	6,179	156,950	5,982	151,950
11 3/4	60.0	0,489	12,421	11,766	298,850	10,772	273,610	6,179	156,950	5,982	151,950
11 3/4	65.0	0,534	13,564	11,766	298,850	10,682	271,320	6,179	156,950	5,982	151,950
13 3/8	54.5	0,380	9,652	13,391	340,130	12,615	320,420	6,179	156,950	5,982	151,950
13 3/8	61.0	0,430	10,922	13,391	340,130	12,515	317,880	6,179	156,950	5,982	151,950
13 3/8	68.0	0,480	12,192	13,391	340,130	12,415	315,340	6,179	156,950	5,982	151,950
13 3/8	72.0	0,514	13,056	13,391	340,130	12,347	313,610	6,179	156,950	5,982	151,950
13 3/8	77.0	0,550	13,970	13,391	340,130	12,275	311,780	6,179	156,950	5,982	151,950
13 3/8	80.7	0,580	14,732	13,391	340,130	12,215	310,260	6,179	156,950	5,982	151,950
13 3/8	85.0	0,608	15,443	13,391	340,130	12,159	308,840	6,179	156,950	5,982	151,950
13 3/8	86.0	0,625	15,875	13,391	340,130	12,125	307,980	6,179	156,950	5,982	151,950