

BLANKING DIM. TS, 09.01.2019, Rev.02, J.Stolz . EL-PIN / IL-PIN geändert , provided: D.Fuchs

Traceability data				Blanking dimensions							
SIZE nominal	WEIGHT nominal	WALL nominal		OD-PIN		ID-PIN		EL-PIN minimal		IL-PIN minimal	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
inch	lb/ft	inch	mm	+ 0,020 - 0	+ 0,50 - 0	+ 0 - 0,020	+ 0 - 0,5	inch	mm	inch	mm
2 3/8	4.60	0,190	4,826	2,383	60,530	1,949	49,500	3,104	78,830	2,907	73,830
2 3/8	5.10	0,218	5,537	2,383	60,530	1,939	49,250	3,104	78,830	2,907	73,830
2 3/8	5.80	0,254	6,452	2,383	60,530	1,867	47,420	3,104	78,830	2,907	73,830
2 7/8	6.40	0,217	5,512	2,883	73,230	2,396	60,850	3,419	86,850	3,222	81,850
2 7/8	7.70	0,276	7,010	2,883	73,230	2,323	59,000	3,419	86,850	3,222	81,850
2 7/8	8.60	0,308	7,823	2,883	73,230	2,259	57,380	3,419	86,850	3,222	81,850
2 7/8	9.80	0,340	8,636	2,883	73,230	2,151	54,640	3,419	86,850	3,222	81,850
3 1/2	7.70	0,216	5,486	3,513	89,230	3,035	77,100	3,864	98,150	3,667	93,150
3 1/2	9.20	0,254	6,452	3,513	89,230	2,992	76,000	3,864	98,150	3,667	93,150
3 1/2	10.20	0,289	7,341	3,513	89,230	2,922	74,220	3,864	98,150	3,667	93,150
3 1/2	12.70	0,375	9,525	3,513	89,230	2,750	69,850	3,864	98,150	3,667	93,150
3 1/2	13.70	0,413	10,490	3,513	89,230	2,674	67,920	3,864	98,150	3,667	93,150
3 1/2	14.70	0,449	11,405	3,513	89,230	2,602	66,090	3,864	98,150	3,667	93,150
3 1/2	15.80	0,476	12,090	3,513	89,230	2,548	64,720	3,864	98,150	3,667	93,150
4	9.50	0,226	5,740	4,013	101,930	3,518	89,350	4,118	104,600	3,921	99,600
4	10.90	0,299	7,595	4,013	101,930	3,476	88,290	4,118	104,600	3,921	99,600
4	13.00	0,330	8,382	4,013	101,930	3,340	84,840	4,118	104,600	3,921	99,600
4	14.80	0,380	9,652	4,013	101,930	3,240	82,300	4,118	104,600	3,921	99,600
4	16.50	0,430	10,922	4,013	101,930	3,140	79,760	4,118	104,600	3,921	99,600
4 1/2	10.50	0,224	5,690	4,516	114,700	4,010	101,850	4,559	115,800	4,362	110,800
4 1/2	11.60	0,250	6,350	4,516	114,700	4,000	101,600	4,559	115,800	4,362	110,800
4 1/2	12.60	0,271	6,883	4,516	114,700	3,958	100,530	4,559	115,800	4,362	110,800
4 1/2	13.50	0,290	7,366	4,516	114,700	3,920	99,570	4,559	115,800	4,362	110,800
4 1/2	15.10	0,337	8,560	4,516	114,700	3,826	97,180	4,559	115,800	4,362	110,800
4 1/2	16.90	0,380	9,652	4,516	114,700	3,740	95,000	4,559	115,800	4,362	110,800
4 1/2	18.80	0,380	9,652	4,516	114,700	3,640	92,460	4,559	115,800	4,362	110,800
4 1/2	21.60	0,500	12,700	4,516	114,700	3,500	88,900	4,559	115,800	4,362	110,800
4 1/2	24.60	0,560	14,224	4,516	114,700	3,380	85,850	4,559	115,800	4,362	110,800